# **HP Designjet T3500 Production eMFP**



The most productive large-format color MFP1—prints up to size E/A0



## All your workflow needs in a highproductivity MFP

- Be the fastest—print D/A1-size pages in 21 seconds with dark blacks. neutral grays, and vivid colors<sup>1</sup>
- Print out your first page right away thanks to ultra-fast processing and zero warm-up time
- Copy and scan guickly with advanced features—presets, batch scanning, multipage PDFs, and scan to email
- Stay organized and avoid clutter—the integrated 100-page stacker delivers prints and copies neatly collated

### A production printer for unattended, low-cost use

- Print your black-and-white drawings at the same cost per page as comparable black-and-white LED MFPs2
- Operate unattended thanks to two heavy rolls of up to 650 ft (200 m) and a total ink capacity of 1,800 ml
- Built for high-volume printing—rely on a robust design to fulfill the most demanding jobs
- Manage projects and control costs effectively, using embedded professional accounting features

## Built for rigorous IT demands and top security

- Minimize device-management tasks and costs, using the HP Designjet Universal Print Driver
- Manage your fleet with ease, while saving time and helping to reduce costs, thanks to HP Web Jetadmin
- Protect and manage confidential jobs securely—retrieve documents at the printer with a personal PIN
- Safeguard confidential information, using a self-encrypting HDD with AES-256, Secure Disk Erase, and IPsec

#### **Eco Highlights**



- Half the energy consumption per plot than equivalent black-and-white LED MFPs:
- ENERGY STAR® qualified and EPEAT Bronze registered²
- Free, convenient HP ink cartridge and printhead recycling<sup>3</sup>
- FSC®-certified papers and a range of recyclable HP media with a take-back program<sup>3</sup>





- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per minute. EPEAT registered where applicable and/or supported. See epeat.net for registration status by country.
- Program availability varies. Please check hp.com/recycle for details. BMG trademark license code FSC\*-C115319, see fsc.org. HP trademark license code FSC\*-C017543, see fsc.org. Not all FSC\*-certified products are available in all regions. For information about HP large format printing materials, please visit globalBMG.com/hp.

Please recycle large-format printing hardware and printing supplies Find out how at our website



- 1. With Aurasma installed, please go to the HP Designjet channel at http://auras.ma/s/ke25m
- 2. Without Aurasma installed, please download it:
  - a. Google Play http://auras.ma/s/android
  - b. Apple Store http://auras.ma/s/ios

Once done, go to the HP Designjet channel at http://auras.ma/s/ke25m

3. Open the application and point to the image to view the HP Designjet vidio

#### Technical specifications

	Line drawings <sup>3</sup>	21 sec/page on A1/D, 120 A1/D prints per hour
	Print resolution	Up to 2400 x 1200 optimized dpi
	Margins (top x	Roll: 3 x 3 x 3 x 3 mm (0.12 x 0.12 x 0.12 x 0.12 in) (borderless on photo papers) ) Sheet: 3 x 22 x 3 x 3 mm (0.12 x 0.87 x 0.12 x 0.12 in)
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)
	Ink cartridges	6 (cyan, gray, magenta, matte black, photo black, yellow)
	Line accuracy	+/- 0.1%4
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)
		0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) <sup>5</sup>
Media	line width Handling	Input: two automatic front-loading roll feeds; smart roll switching; rolls up to
rieula	nanding	200 m (650 ft) long each and 180 mm (7.1 in) of diameter; sheet feed Output: integrated output stacker (from A4/A to A0/E, with up to 100 A1/D-size capacity); media bin; automatic cutter
	Size	Scanner: straight-through scan paper path for sheet and cardboard originals Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in)
	Thirdren	Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)
<b>.</b>	Thickness	Up to 0.5 mm (19.7 mil)
Scan	Scan speed	Color: up to 6.35 cm/sec (2.5 in/sec) Grayscale: up to 19.05 cm/sec (7.5 in/sec)
	Scan/copy resolution	Up to 600 dpi
	Maximum scan	Size: 914 x 8000 mm (36 x 315 in) (JPEG)
		914 x 5000 mm (36 x 197 in) (PDF) 610 x 15,000 mm (24 x 590.5 in) (TIFF)
	Thickness	Up to 0.8 mm (0.03 in)
Сору	Reduction/	25 to 400%; at 1% increment
	enlargement	
	Maximum copies	Up to 99 copies
	Copier settings	Copy quality, copy color, roll, paper output, content type, original paper type, background removal, contrast, de-skew, blueprints support, copy margin layout,
Applications	Line drawings Reno	full width, job queue storage mode lerings, Presentations, Maps, Orthophotos
Memory		processor, 128 GB (virtual), 6 500 GB hard disk (AES-256 encrypted, FIPS
ricinory	140-2 Level 2 certi	
Connectivity	Interfaces (standard)	High-Speed USB 2.0 certified host connector Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4o only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, FTP, WS Discovery, Embedded Web Server(HTTP, HTTPs), IPSec, SMTP (e-mail), Raw IP printing (9100, 9101, 9102), LPD, IPP, WS
	Deightlessesses	print, NTLM, NTLM v2, SSL/TLS, 802.1X authentication (WEP, WPA, WPA2, LEAP, PEAP, EAP-TLS)
	Print languages (standard)	HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI
	Print languages (optional)	Adobe PostScript 3; Adobe PDF 1.7
	Printing paths	HP Designjet SmartStream (optional), Printer driver, HP Embedded Web Server, direct printing from USB flash drive, email printing
	Drivers (included)	HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScrip Windows and Mac drivers with optional PostScript/PDF Upgrade Kit. Compatible with HP Designjet Universal Print Driver for HP-GL/2 and HP Designjet Universal
		Print Driver for PS (with PostScript/PDF Ungrade Kit)
Dimensions	Printer	Print Driver for PS (with PostScript/PDF Upgrade Kit)  1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in)
	Printer Shipping	
(w x d x h)		1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in)
(w x d x h) Weight	Shipping Printer Shipping	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb)
(w x d x h) Weight What's in the	Shipping Printer Shipping HP Designjet T3500 printer stand and m	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 146 kg (310.8 lb) 147 kg (310.8 lb) 148 kg (310.8 lb) 149 kg (310.8 lb) 140 kg (310.8 lb)
(w x d x h) Weight What's in the	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) edFP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster over cord
(w x d x h) Weight What's in the box Environmental	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 146 kg (310.8 lb) 147 kg (310.8 lb) 148 kg (310.8 lb) 149 kg (310.8 lb) 140 kg (310.8 lb)
(w x d x h) Weight What's in the box Environmental	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po Operating temperature	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) edFP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster over cord
(w x d x h) Weight What's in the box Environmental ranges	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po Operating temperature Storage temperature Operating humidity	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 14FP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster were cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH
(w x d x h) Weight What's in the box Environmental ranges	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, pot Operating temperature Storage temperature Operating humidity Sound pressure	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) eMFP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster over cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep)
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, pc 1 Operating temperature Storage temperature Operating humidity Sound pressure Sound power	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) eMFP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster over cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep)
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) eMFP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster were cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); o watts (off)
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, pc 1 Operating temperature Storage temperature Operating humidity Sound pressure Sound power	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 14H RP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster over cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) <120 watts (printing); < 2 watts (< 7 watts with embedded Digital Front End)
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 142 kg (310.8 lb) 143 kg (310.8 lb) 144 kg (310.8 lb) 145 kg (310.8 lb) 146 kg (310.8 lb) 147 kg (310.8 lb) 148 kg (310.8 lb) 149 kg (310.8 lb) 140 kg (310.8 lb) 140 kg (310.8 lb) 140 kg (310.8 lb) 141 kg (310.8 lb) 142 kg (310.8 lb) 143 kg (310.8 lb) 144 kg (310.8 lb) 145 kg (310.8 lb) 146 kg (310.8 lb) 147 kg (310.8 lb) 148 kg (310.8 lb) 148 kg (310.8 lb) 149 kg (310.8 lb) 140 kg (310.8 lb) 140 kg (310.8 lb) 140 kg (310.8 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 142 kg (310.8 lb) 143 kg (310.8 lb) 144 kg (310.8 lb) 145 kg (310.8 lb) 145 kg (310.8 lb) 146 kg (310.8 lb) 146 kg (310.8 lb) 147 kg (310.8 lb) 148 kg (310.8 lb) 148 kg (310.8 lb) 149 kg (310.8 lb) 140 kg (310.8
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, pc 1 Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) eMFP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster over cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 4.120 watts (printing); 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KC) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand RSM), China (CCC), Japan
Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic Power Certification	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 1141 kg (310.8 lb) eMFP, printhead, introductory ink cartridges, stacker, scanner calibration sheet, edia bin, spindles, 3-in spindle adapter kit (x2), quick reference guide, setup poster over cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) <120 watts (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (RAM); Mexico (NYCE); Korea (KC) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES),
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Shipping Printer Shipping HP Designjet T3500 printer stand and m startup software, po Operating temperature Storage temperature Operating humidity Sound pressure Consumption Requirements Safety Electromagnetic	1400 × 784 × 1109 mm (55.1 × 30.9 × 43.7 in) 1502 × 780.5 × 804 mm (59.1 × 30.7 × 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 142 kg (310.8 lb) 143 kg (310.8 lb) 144 kg (310.8 lb) 145 kg (310.8 lb) 146 kg (310.8 lb) 147 kg (310.8 lb) 148 kg (310.8 lb) 149 kg (310.8 lb) 149 kg (310.8 lb) 140 kg (41 kg (310.8 lb) 150 kg (310.8 lg) 150 kg (310.8

#### **Ordering information**

Product	B9E24A	HP Designjet T3500 36-in Production eMFP <sup>7</sup>
	B9E24B	HP Designjet T3500 36-in Production eMFP <sup>8</sup>
Accessories	COC66A	HP Designjet PostScript/PDF Upgrade Kit
	G8B09A	HP Designjet T3500 36-in Spindle
	E2P02A	HP SmartStream Preflight Manager for HP Designjet
	E2W16A	HP SmartStream Print Controller for HP Designjet T3500 Production eMFP
Original HP printheads	B3P06A	HP 727 Designjet Printhead
Original HP	C1Q13A	HP 764 300-ml Cyan Designjet Ink Cartridge
ink cartridges	C1Q14A	HP 764 300-ml Magenta Designjet Ink Cartridge
	C1Q15A	HP 764 300-ml Yellow Designjet Ink Cartridge
	C1Q16A	HP 764 300-ml Matte Black Designjet Ink Cartridge
	C1Q17A	HP 764 300-ml Photo Black Designjet Ink Cartridge
	C1Q18A	HP 764 300-ml Gray Designjet Ink Cartridge
Original HP large format printing	C6810A	HP Bright White Inkjet Paper (FSC® certified) <sup>9</sup> 🛟 10 914 mm x 91.4 m (36 in x 300 ft)
materials	C6980A	HP Coated Paper (PEFC™ certified)³ 🏰 ⁰ 914 mm x 91.4 m (36 in x 300 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) <sup>9</sup> 🛟 10 914 mm x 30.5 m (36 in x 100 ft)
	Q1421B	HP Universal Satin Photo Paper 914 mm x 30.5 m (36 in x 100 ft)

### Service and support<sup>11</sup>

H4518E	HP Installation Service with Network Setup
U1ZX9E	HP 3 year Next Business Day Onsite Support with DMR <sup>12, 13</sup>
U1ZY0E	HP 5 year Next Business Day Onsite Support with DMR <sup>13</sup>
U1ZY1PE	HP 1 year Post Warranty, Next Business Day Onsite Support with DMR <sup>13</sup>
U1ZY2PE	HP 2 year Post Warranty, Next Business Day Onsite Support with DMR <sup>13</sup>
U1XV4E	HP Preventive Maintenance Service

HP Designjet Support Services offer solutions for business critical environments – installation, extended support and maintenance, as well as variety of value-added services. For more information, please visit hp.com/go/designjet/support.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays. 14 For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

- <sup>1</sup> Compared with large-format color MFPs under \$25,000 USD. Based on the fastest-rated color speeds as published by manufacturers as of January 2014. Test methods vary.
- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per minute.
- Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (Bond) and Original
- +/- 0.1% of the specified vector length or +/- 0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on AO/E HP Matte Film in Best or Narmal mode with Original HP inks.
- Measured on HP Matte.Film.
- 6 Based on 2.5 GB RAM.
- 90-day limited hardware warranty. (US and Canada).
- <sup>8</sup> Three-year limited hardware warranty. (US and Canada): One-year limited hardware warranty. (Latin
- BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. BMG trademark license code PEFC™/29-31-261, see <u>pefc.org</u>. HP trademark license code PEFC™/29-31-198, see pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.
- 10 Can be recycled through commonly available recycling programs.
- 11 HP Service portfolio available only for B9E24B HP Designjet T3500 36-in Production eMFP, HP Service portfolio not available in Latin America.
- <sup>12</sup> This HP Service not available in US and Canada.
- $^{13}\ \ \text{Defective Media Retention keeps your sensitive data safe}. \ \text{To comply with security regulations you can keep the}$  $defective\ hard-drive\ or\ data-retentive\ memory\ component\ while\ getting\ a\ new\ replacement\ disk\ or\ memory.$
- True neutral grays produced by printers compatible with the HP Three-black ink set.















#### For more information, please visit

hp.com/go/DesignjetT3500



# บริษัท บีพีเอส ยูในเต็ด จำกัด

213 หมู่ 1 ถนนสุขสวัสดิ์ ตำบลปากคลองบางปลากด อำเภอพระสมุทรเจดีย์ สมุทรปราการ 102% T. 0-2816-3888, 0-2816-3999, 0-91818-2988-9 F. 0-2816-3838-9 www.bpsunited.com, www.facebook.com/bpsunited

