HP Designjet D5800 Production Printer



The fastest 60-inch dye-ink production printer for nonstop operation¹



Easy integration into your low-cost environment

- Seamlessly integrate this printer into your current environment and continue using the inks you rely on
- Keep printing costs low—stock one dual-channel printhead SKU optimized for HP dye inks—use it for any color
- Create prints with excellent color transitions and grain thanks to a new printhead with a small drop size²
- Increase your productivity with simple media-handling features that help keep media flat while printing

High-speed operation—around the clock

- High-speed printing—up to 128 m²/hr in Fast mode and 24 m²/hr in Production mode for polypropylene³
- Create quality prints at top speed, using HP Double Swath Technology and the HP Optical Media Advance Sensor
- Expand your offerings—print backlit graphics, POP signs, roll-up banners, and indoor signs in vivid color
- Confidently run jobs overnight with a printhead status gauge, long roll support, and solid take-up reel⁴

Robust design and easy maintenance

- Depend on robust, durable design features built to handle the most demanding printing environments
- Easily maintain your printer in-house with the easy-to-replace printhead and automatic printhead cleaning
- Increase printer uptime with certified reseller support designed to resolve printer issues fast
- Invest in a reliable, workhorse printer backed by a one-year warranty

Eco Highlights

- Breakthrough color consistency can help reduce unnecessary reprints
- FSC®- certified papers,¹ range of recyclable HP media with a take-back program
- BMG trademark license code FSC*-C115319, see fsc.org. HP trademark license code FSC*-C017543, see fsc.org. Not all FSC*-certified products are available in all regions. For information about HP large format printing materials, please visit globalBMG.com/hp.
 Program availability varies. Please check <u>hp.com/recycle</u> for details.



Please recycle large-format printing hardware and printing supplies Find out how at our website

- Compared with large-format inkjet printers under \$23,000 USD for 60- to 64-inch graphic dye applications and based on list price, China. Based on the fastest-rated color speeds published by
- manufacturers in January 2014. Test methods vary. The HP 706 Printhead used in the HP Designjet D5800 Production Printer delivers a 50% smaller drop size than the HP Designjet 5100 Printer printheads.
- 3 The HP Designjet D5800 Production Printer can achieve speeds up to 128 m 2 /hr when used in Fast mode on plain paper and can achieve print speeds up to 24 m 2 /hr in Fast mode with EconoMode on using polypropylene media.
- ⁴ Take-up reel purchased separately.

Technical specifications

| Print | Max print speed ⁵ | 128 m²/hr (1378 ft²/hr) on plain media |
|------------------------------|---|---|
| | Color images ⁶ | Best: 3.53 min/page on A1/D or up to 12.4 m²/hr (133 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/hr (195 ft²/hr) on glossy media Normal: 2.51 min/page on A1/D or up to 18.17 m²/ |
| | Print resolution | Up to 2400 x 1200 optimized dpi |
| | Margins | 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) |
| | Ink types | Dye-based |
| | Ink cartridges | Cyan, magenta, yellow, black |
| | Line accuracy | +/- 0.1%7 |
| | Minimum line width | 0.02 mm (0.0008 in) (HP-GL/2 addressable) |
| lmage | Color accuracy | Median < 1.6 dE2000, 95% of colors < 3.75 dE2000 ⁸ |
| quality | Short-term color stability | < 1 dE2000 in less than 5 minutes ⁹ |
| | Long-term print-to-print repeatability | Average < 0.5 dE2000, 95% of colors < 1.25 dE2000° |
| | Maximum optical density | 6 L* min/2.15 D ¹⁰ |
| Media | Handling | Roll feed, automatic cutter |
| | Media types | $\label{thm:control} Coated paper, technical paper, photographic paper, backlit, self-adhesive banner and sign$ |
| | Size | 279 to 1524-mm (11 to 60-in) rolls |
| | Thickness | Up to 0.56 mm (22 mil) |
| Applications | Posters, POP/POS, E | Banners, Mockups, Photos, Light boxes – film, Proofs, Displays |
| Memory | 64 GB (virtual) ¹¹ , 320 |) GB hard disk |
| Connectiv- ity | Interfaces (standard) | Gigabit Ethernet (1000Base-T), EIO Jetdirect accessory slot |
| | Print languages (standard) | HP-GL/2, HP-RTL, CALS G4 |
| | Print languages (optional) | Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG |
| | Printing paths | Printer driver, HP Embedded Web Server |
| | Drivers (included) | HP-GL/2, HP-RTL drivers for Windows; PostScript Windows and Mac drivers with optional PostScript/PDF Upgrade Kit |
| Dimensions (w x d x h) | Printer | 2430 x 690 x 1370 mm (95.7 x 27.2 x 53.9 in) |
| | Shipping | 2700 x 750 x 1200 mm (106.3 x 29.5 x 47.2 in) |
| Weight | Printer | 180 kg (397 lb) |
| | Shipping | 213 kg (470 lb) |
| What's in the box | HP Designjet D5800 Production Printer, spindle, printheads, maintenance cartridge, printer stand, 3-in spindle adapter kit, quick reference guide, setup poster, startup software, power cord | |
| Environ- mental ranges | Operating temperature | 5 to 40°C (41 to 104°F) |
| | Storage temperature | -20 to 55°C (-4 to 131°F) |
| | Operating humidity | 20 to 80% RH |
| Acoustic | Sound pressure | 53 dB(A) (printing); 39 dB(A) (ready); 39 dB(A) (sleep) |
| | Sound power | 7.0 B(A) (printing); 5.5 B(A) (ready); 5.5 B(A) (sleep) |
| Power | Consumption | 270 watts (printing); < 48 watts (ready); < 5.3 watts (sleep); < 0.3 watts (off) |
| | Requirements | Input voltage (auto ranging): 100 to 127 VAC (+/- 10%), 5 A; 220 to 240 VAC (+/- 10%), 3 A; 50/60 Hz (+/- 3 Hz) |
| Certification | Safety | USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (G0ST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC) |
| | Electromagnetic | Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP), Korea (MSIP) |
| | Environmental | ENERGY STAR, WEEE, RoHS (EU, China, Korea, India), REACH |
| | One-year limited ha | |











Ordering information

| | F2I 45A | HP Designjet D5800 60-in Production Printer |
|--|------------------|--|
| Product Accessories | CQ745B | HP Designjet PostScript/PDF Upgrade Kit |
| | CQ754A | HP Designjet 60-in Spindle |
| | J8025A | HP Jetdirect 640n Print Server |
| | 06715A | HP Designjet User Maintenance Kit |
| | - | |
| | J6E61A J6E62A | HP Designjet D5800 Take-up Reel |
| | | HP Designjet Media Edge Holder |
| Original HP printheads | F9J49A | HP 706 Designjet Printhead |
| | CH644A | HP 771 Designjet Maintenance Cartridge |
| Original HP ink artridges | C4930A | HP 81 680-ml Black Ink Cartridge |
| curtinges | C4931A | HP 81 680-ml Cyan Ink Cartridge |
| | C4932A | HP 81 680-ml Magenta Ink Cartridge |
| | C4933A | HP 81 680-ml Yellow Ink Cartridge |
| | C5066A | HP 81 680-ml Black 3-ink Multipack |
| | C5067A | HP 81 680-ml Cyan 3-ink Multipack |
| | C5068A | HP 81 680-ml Magenta 3-ink Multipack |
| | C5069A | HP 81 680 ml Yellow 3-ink Multipack |
| Original HP large format printing materials | COF22A | HP Everyday Adhesive Matte Polypropylene, 2 Pack 1524 mm x 22.9 m (60 in x 75 ft) |
| | CH027A | HP Everyday Matte Polypropylene, 2 Pack 🛟 12 1524 mm x 30.5 m (60 in x 100 ft) |
| | Q6578A | HP Universal Instant-dry Gloss Photo Paper (FSC® certified) ¹³ 🏰 ¹⁴ 1524 mm x 30.5 m (60 in x 100 ft) |
| | Q6583A | HP Universal Instant-dry Satin Photo Paper (FSC® certified) ¹³ 🛟 ¹⁴ 1524 mm x 30.5 m (60 in x 100 ft) |
| | Q1428B | HP Universal Gloss Photo Paper 1067 mm x 30.5 m (42 in x 100 ft) |
| | Q1422B | HP Universal Satin Photo Paper 1067 mm x 30.5 m (42 in x 100 ft) |
| | Q8750A | HP Premium Vivid Color Backlit Film 🏰 1524 mm x 30.5 m (60 in x 100 ft) |
| | C6568B | HP Coated Paper (PEFC™ certified) ¹³ ♣\$ 5 1372 mm × 45.7 m (54 in × 150 ft) |
| | Q1398A | HP Universal Bond Paper (FSC® certified) ¹³ 🍑 ¹⁵ 1067 mm x 45.7 m (42 in x 150 ft) |
| | C6977C | HP Heavyweight Coated Paper (PEFC™ certified) ¹³ 🎝 ¹⁵ 1524 mm x 30.5 m (60 in x 100 ft) |

Service and support

| H4518E | HP Installation Service with Network Setup | |
|---------|--|--|
| U1XV5E | HP 2 year Next Business Day Onsite Support with DMR ¹⁶ | |
| U1XV6E | HP 3 year Next Business Day Onsite Support with DMR ¹⁶ | |
| U1XV7E | HP 5 year Next Business Day Onsite Support with DMR ¹⁶ | |
| U1ZM3PE | HP 1 year Post Warranty, Next Business Day Onsite Support with DMR ¹⁶ | |
| U1ZM2PE | HP 2 year Post Warranty, Next Business Day Onsite Support with DMR ¹⁶ | |
| HIIVME | LID Drawantiwa Maintananca Carvica | |

For the entire HP Large Format Printing Materials portfolio, please see $\underline{\mathsf{globalBMG.com/hp.}}$

- ⁵ Mechanical printing time. Printed in Fast mode with Economode on with Original HP inks.
- ⁶ Mechanical printing time. Printed with Original HP inks.
- 7 +/- 0.1% of the specified vector length or +/- 0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original HP inks.
- 8 ICC absolute colorimetric accuracy on HP Premium Instant-dry Gloss Photo Paper with Original HP inks.
- 9 With HP Premium Instant-dry Gloss Photo Paper with Original HP inks, right after calibration.
- ¹⁰ With HP Premium Instant-dry Gloss Photo Paper with Original HP inks.
- Based on 1 GB RAM. Expandable to 1.5 GB RAM through an HP Designjet qualified SODIMM included only in the optional HP Designjet PostScript/PDF Upgrade Kit accessory.
- ¹² HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See <u>globalBMG.com/hp/ecosolutions</u> for details.
- BMG trademark license code FSC®-C115319, see <u>fsc.org</u>. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. BMG trademark license code PEFC™/29-31-261, see <u>pefc.org</u>. HP trademark license code PEFC™/29-31-198, see <u>pefc.org</u>. Not all FSC®- or PEFC™-certified products are available in all regions.
- In Asia (including Japan), recyclable in consumer collection systems that can accept mixed paper (may not be recyclable in your area).
- 15 Can be recycled through commonly available recycling programs.
- Defective Media Retention keeps your sensitive data safe. To comply with security regulations you can keep the defective hard-drive or data-retentive memory component while getting a new replacement disk or memory.



บริษัท บีพีเอส ยูในเต็ด จำกัด 213 หมู่ 1 ถนนสุขสวัสดิ์ ตำบลปากคลองบางปลากด อำเภอพระสมุทรเจดีย์ สมุทรปราการ 10290

213 หมู่ 1 กนนสุขสวัสดิ์ ตำบลปากคลองบางปลากด อำเภอพระสมุทรเจดีย์ สมุทรปราการ 1029 T. 0-2816-3888, 0-2816-3999, 0-91818-2988-9 F. 0-2816-3838-9 www.bpsunited.com, www.facebook.com/bpsunited



J6E62A